



High Performance Doors

Speed-Commander™ 1200 Dock-Master / Screen-Master®

Speed-Commander™ 1400 SEL Series

Speed-Master® 1600 L • 2600 L • 4500

Speed-Guardian™ 4000 U



Product Application Data



Ask for our detailed brochure	Speed-Commander™ 1200	Speed-Commander™ 1400 SEL				Speed-Master®			Speed-Guardian™
	Dock-Master / Screen-Master®	1400 SEL	Clean-Master 20 Pa	Cool-Master	Food-Master	1600 L	2600 L	4500	4000 U
Application	Interior / Exterior	Interior	Interior/ Clean room	Interior/ Cooler	Interior/ Wash-down	Interior / Exterior			Interior / Exterior
Max. width	Int. openings: 14'0" Ext. openings: 10'0"	14'0"	10'0"	14'0"	14'0"	14'0"	20'0"	32'0"	22'0' 16'0" with full-view option
Max. height	Int. openings: 14'0" Ext. openings: 10'0"	16'0"	10'0"	16'0"	16'0"	16'0"	24'0"	Total 675 sq. ft.	20'0' 16'0" with full-view option
Wind pressure	Up to 35 mph	Up to 25 mph	Up to 25 mph	Up to 25 mph	Up to 25 mph	Up to 60 mph	Up to 60 mph		Hurricane rated q2 2012
Opening speed	Up to 14" / sec.	Up to 80" / sec.	Up to 80" / sec.	Up to 80" / sec.	Up to 80" / sec.	Up to 60" / sec.	Up to 36" / sec.	Up to 24" / sec.	Up to 80" / sec.
Closing speed	Up to 14" / sec.	30" / sec.	30" / sec.	30" / sec.	30" / sec.	30" / sec.		24" / sec.	18" / sec.
Motor	Self-monitoring Direct-drive	Self-monitoring direct-drive / variable speed / frequency convertor			Self-monitoring direct-drive variable speed / frequency convertor Optional: NEMA 4x	Self-monitoring direct-drive / variable speed / frequency convertor		Direct-drive	Self-monitoring direct-drive variable speed frequency convertor
Control Box	Standard	Basic non-timer	HFCB 1-phase hardwired			Up to 10 x 10: HFCB 1-phase hardwired	Hardwired UL/CUL 3-phase	Hardwired 3-phase	Smart Start™ HFC1
	Optional	Automatic closing	HFC1 hardwired 3-phase or Smart Start™ HFC1			Over 10 x 10: 3-phase UL or HFC1 3-phase hardwired or Smart Start™ HFC1	Smart Start™ HFC1	N/A	N/A
Voltage	Standard	230 v / 3 phase / 60 Hz	230 v / 1-phase / 60 Hz / 3-phase output power requirement				230 v or 460 v / 3-phase / 60 Hz	230 v or 460 v / 3-phase / 60 Hz	230 v or 460 v / 3-phase / 60 Hz
	Optional	N/A	230 v or 460 v / 3-phase / 60 Hz				N/A	N/A	N/A
Guide Tracks	Standard	Galvanized steel			Stainless steel	Galvanized with removable covers	Galvanized & hinged		Galvanized
	Optional	Stainless steel			Galvanized steel	N/A			
Panel material	Int. openings: PVC nylon-reinforced Ext. openings: High impact tear resistant Opt: Polyester screen	PVC nylon-reinforced	3 mm foam fabric	Standard: 40 oz. / sq. yd. nylon reinforced PVC Optional: 90 oz. / sq. yd. FDA approved polyurethane	90 oz. / sq. yd. Bulldog XT			Hot-dipped galvanized steel with urethane foam core	
Colors available	Int. openings: Orange, blue, yellow, red, gray Ext. openings: Black, blue Opt: Royal blue screen	Orange, blue, yellow, red, gray	Gray	White	Orange, blue, black, gray			Standard: Silver Optional: All RAL colors	
Vision area	Optional: Full-width	Standard: Full-width x 35" high	Optional: Full-width x 35" high	Optional: Full-width x 35" high only available with the 40 oz. PVC panel	Two full-width			Optional vision panels available	
Reversing edge	Not required	Not required					Yes	Not required	
Light grid	Optional	Built into guide tracks 8'0"					N/A	Built into guide tracks 8'0"	
Photocell		N/A					Yes	N/A	
Warranty on panel material	3 years	2 years			5 years			5 years	
Warranty on motor	3 years 1 year on all other components	5 years on motor and fabric - 2 years on all other components							



Hörmann Flexon LLC • Buncher Commerce Park • Avenue C • Building 20A • Leetsdale, PA 15056-1376
 Phone: 800.365.3667 • 724.385.9150 • Fax: 724.385.9151 • www.hormann-flexon.com • Email: sales@hormann-flexon.com

We reserve the right to change specifications without notice. Printed in USA. ©Hörmann Flexon LLC (Issue 1.2012 / Johnson-Print 1.2012)

