



Speed-Commander™ 1400 SEL Technologically advanced

Built-in light grid, single phase connection, sectional panel design



Built-in light grid

Standard on the Speed-Commander™ 1400 SEL is a light grid built into the guide tracks up to 8'0" high. Completely free of coil cords, the light grid provides a thorough wall of protection for personnel and equipment at the doorway, as compared to other doors that use only photocells. Full perimeter draft seals provide dust and odor containment, as well as general environmental control.



Single phase connection / 3-phase drive

The Speed-Commander™ 1400 SEL accommodates the standard power sources readily available in most facilities. The HFCB control box is hardwired and standard with a 230 v / 1-phase / 60 Hz / 3-phase output power requirement. Optional are both the HFC1 3-phase, hardwired control box and the proven and tested Smart Start™ HFC1 3-phase control box when UL approval and ultimate operational speed is required.



Sectional panel design

The Speed-Commander™ 1400 SEL comes in a sectional panel design. The panels are connected using aluminum profiles and have specially designed edges that allow the panels to slide easily into the horizontal aluminum profiles for fast replacement.



Proven and tested features

- Application: Interior door openings up to 14'0" wide x 16'0" high.
- Operating Speed: Up to 80" per second up and 30" per second down.
- Panel: 1/16" thick reinforced PVC. Colors: orange, blue, yellow, red and gray.
- Vision: Full-width, clear PVC starting approximately 52" off floor.
- Motor: Compact, self monitoring direct-drive motor has a patented built-in catch system and is maintenance free.
- Protection / Self-Repairing: The unique SoftEdge bottom profile offers maximum protection. After a collision, the door stops instantly and the SoftEdge profile is fed back into the guide tracks with the push of a button. As a self-repairing system, this prevents downtime and service calls.



The motor / gearbox (excluding catch) and panel material are guaranteed to be free of defects in materials and workmanship for 5 years. All other mechanical and electrical components are warranted to be free of defects for 2 years.



Ask for our detailed brochure

