



3&1
WARRANTY
YEAR

Speed-Commander™ 1200 Dock-Master / Screen-Master®

Economical high performance door for loading dock door openings,
dumpster doorways and platform docks



Speed-Commander™ 1200 Dock-Master

Economical solution for low-frequency use

Features

Application	Interior or exterior
Model / Classification	1200 Dock-Master-Screen-Master® / Fabric
Size range	Exterior openings maximum 10'0" w x 10'0" h Interior openings and doors with screen panels maximum 14'0" w x 14'0" h
Technology	Direct-drive, sectional panel
Operating speed	Opening 14" IPS Closing 14" IPS
Panel	Patented, sectional design, heavy-duty aluminum hinge profiles <u>Panel interior openings:</u> Reinforced, puncture resistant 58 oz. PVC material Colors: orange, blue, yellow, red, gray and white <u>Panel exterior openings:</u> Reinforced, puncture resistant 40 oz. vinyl Colors: blue, black <u>Optional:</u> High-strength, royal blue polyester mesh screen, 10 oz. / sq. yd., 17 x 11 thread count
Vision	One full-width, clear PVC starting approximately 52" off floor
Custom panel imprints	Logos, photos or text Digitally printed onto panel UV treated and waterproof Maximum image size 7'0" wide X 3'0" high
Resistance to wind load	Consult factory
Guide tracks	12 ga. hot-dipped galvanized steel One-piece with removable front cover: 7-1/4" wide X 4-1/2" projection
Hoods	Optional: Galvanized steel
Safety	Optional: 8'0" high light grid built into guide tracks when automatic closing required
Control	NEMA 3S Non-timer 110 v 1-phase or 230 v 3-phase / 60 Hz voltage input
Activation	Constant contact push button
Emergency	Hand crank Optional: Chain hoist
Compliance	Door complies with requirements of UL325
Warranty	3 & 1 Year: Motor and panel material 3 years, materials & workmanship All other mechanical and electrical components free from defects, 1 year

Available Power Choices

110 v / 1-phase:

Screen panel - Less than 10' x 10'
40 oz. vinyl panel - Less than 8' x 8'
58 oz. vinyl panel - Less than 10' x 10'

230 v / 3-phase:

Screen panel - Up to 14' x 14'
40 oz. vinyl panel - Up to 10' x 10'
58 oz. vinyl panel - Up to 14' x 14'

Simple design with flexible power choices

The 1200 is a heavy-duty roll-up door intended for low-frequency use and opens / closes with a constant pressure push button at a speed of 14" per second. The basic non-timer control box is available for either 110 v / 1 phase or 230 v / 3 phase 60 Hz power requirements. When automatic closing is required, an optional built-in light grid is included.



Optional Screen-Master® mesh material for ventilation

The Dock-Master / Screen-Master® comes in a sectional panel design. The panels are connected using aluminum hinge profiles which allow for fast panel replacement when required. High-strength, polyester mesh screen material can be interchanged with the solid panels for ventilation during the warmer months. The panel sections can be easily interchanged without special tools.

HÖRMANN



Hörmann Flexon LLC • Starpointe Business Park • 117 Starpointe Boulevard • Burgettstown, PA 15021-9506
Phone: 800.365.3667 • 724.385.9150 • Fax: 724.385.9151 • www.hormann-flexon.com • Email: info2@hormann.us

We reserve the right to change specifications without notice. ©Hörmann Flexon LLC (Issue 06.2018) Print