



5&2  
WARRANTY  
YEAR

# Speed-Commander™ 1400 SEL Cool-Master

High performance door ideal for cooler applications  
Interior door openings up to 14'0" w x 16'0" h



# Speed-Commander™ 1400 SEL Cool-Master

Cooler door openings up to 14'0" w x 16'0" h

## Features

|                         |   |
|-------------------------|---|
| Application             | Interior  |
| Model / Classification  | 1400 SEL Cool-Master / Fabric   |
| Size range              | Maximum 14'0" w x 16'0" h<br>(A hood may be required depending on location. Consult factory)  |
| Technology              | Direct-drive, sectional panel   |
| Operating speed         | Opening 80" IPS<br>Closing 30" IPS  |
| Panel                   | Patented, sectional design, heavy-duty aluminum hinge profiles<br>Panel: reinforced, puncture resistant 3 mm thick foam material<br>Color: gray   |
| Vision                  | One full-width, clear PVC starting approximately 52" off floor  |
| Custom panel imprints   | Logos, photos or text<br>Digitally printed onto panel<br>UV treated and waterproof<br>Maximum image size 7'0" wide X 3'0" high  |
| Resistance to wind load | Consult factory   |
| Guide tracks            | 12 ga. hot-dipped galvanized steel<br>One-piece with removable front cover:<br>7-1/4" wide X 4-1/2" projection  |
| Hoods                   | Optional: Galvanized steel or stainless steel   |
| Safety                  | 8'0" high light grid built into guide tracks  |
| Control                 | NEMA 4X Smart Start™ NXT<br>208 to 575 v / 3-phase / 60 Hz voltage input<br>Optional: HFCB NEMA 3 Smart Start NXT<br>230 v / 1-phase 60 Hz voltage input<br>Optional: UPS emergency battery pack<br>(Requires use of HFCB 1-phase control box). |
| Activation options      | Push button / Pull cord / Motion detector / Presence detector<br>Induction loop detector (wire/sealant by others) / Remote control<br>Touchless switch (several models)<br>Consult factory for additional options                               |
| Accessories             | LED Lite-Advance / SmartControl M2M / ScanProtect /<br>Wireless Crash Alert / Customized energy analysis report   |
| Emergency               | Hand crank.<br>Optional: chain hoist  |
| Compliance              | Door complies with requirements of UL325  |
| Warranty                | 5 & 2 Year: Motor/gearbox (excluding catch) and panel material<br>5 years, materials & workmanship<br>All other mechanical and electrical components<br>free from defects, 2 years  |



### Foam panel for optimum energy savings

An advanced 3 mm thick gray foam panel material maintains flexibility to +33° F and helps to keep condensation to a minimum in cooler to ambient areas. Our unique sectional panel design makes it possible to replace panels easily for minimal downtime.



### NEMA 4X Smart Start™ NXT control box simplifies installation

A distribution block accepts the activation and protection device wiring; main power cables feed through pre-drilled holes on the bottom of the box where the individual wires, with pre-wired removable terminal blocks, plug into the circuit board. Extra ports on the control board allowing for firmware upgrades and future expansion. A USB port is available for maintenance monitoring.

