

Product Data Sheet

Speed-Guardian™ 5000 H CV 42

Overhead High-Lift, High-Performance Door with Double-Pane Vision Panels



Features



Speed-Guardian™ High-Lift, high-speed doors provide excellent capability while avoiding obstructions.

- Smart Start™ NXT, NEMA 4X programmable control box.
- Thermally isolated design for reduced heat transfer and optimal energy efficiency.
- Speed: Up to 100"/sec. open, 20"/sec. close.
- Exclusive non-contact guide technology reducing wear and noise.
- Spring-less counterbalance lift assistance.
- Integral, non-contact light grid entrapment protection feature. Ensures safety of equipment, people, and vehicles.
- Emergency operation via chain hoist.
- Obstruction avoidance High-Lift track application for limited clearance.
- Enhanced 10" high double-pane vision slats with Duratec® synthetic glazing.
- Optional tinted vision slats, Obscured White, Smoke Gray.
- Optional perforated metal slats for ventilation requirements.
- 5, 2, & 7 year warranty protection plan. 5 yrs. motor/gearbox and panels. 2 yrs. other mech./elec., 7 yrs. vision slats.

Technical Data		Remark	
Speed-Guardian™ High-Lift 5000 H CV 42			
Rigid, overhead rapid rolling high-performance door with obstruction avoidance technology.			
Application		Exterior	
Speed		Opening 60" up to 100"/sec.	Closing Up to 20"/sec.
Control Panel		Smart Start™ NXT (11 5/8"W x 15 3/4"H x 8 3/16"D)	
Roll-up Technology		Non-contact overhead guides with Non-contact lintel seal	
	Size Range	16'-0" wide, up-to 21'-4" high	
	Guide Track Profile	12" x 12 1/2", chamfered corners (interior side)	
	Distance Back Formula	DB = 2 x DH - (DH + HR min. or any distance up-to HR Max.) + 39 1/2"	
	Solid Slat Height & Depth	9 7/8"H, 1 5/8"D or 14-3/4", 2-5/8"	
	Vision Area Height	6-3/8" or 10"	
Overhead Rolling	Mullions	None up-to 120" wide One up-to 197" wide Two if ≥ 198" wide	
Required Headroom		HR min. = 29-1/4", HR max. = 23'-3"	
Drive Mechanism		Direct-drive operator with chain lift mechanism	
Counterbalance System		Chain mechanism and counterweights	
Braking		Control box activated 24V DC brake	
Cycleability / Maintenance		High / inspect per ea. 50,000 cycles or 6 mo. Windows replacable independent of solid slats	
Actuators		Manually Operated Push Button Stations Touchless Motion/Presence Sensors	
Safety Features		Built-in light grid, chain hoist open/close	
Resistance to Wind Load		DW ≤ 16'-0", Class 5 max. 93mph (21psf; 115mph max.)	
Fire Resistance Rating		Non-rated, Non-conforming exit	
Warranty		5, 2, & 7 years. Motor/gearbox and Panels (5), all other mech./elec. (2), vision slats (7)	

Product Data Sheet (Continued)

Speed-Guardian™ 5000 H CV 42

Overhead High-Lift, High-Performance Door with Double-Pane Vision Panels



Materials and Finishes		
Guide Tracks & Covers	11-ga. HDG steel tracks, 16-ga. HDG steel covers	Zinc, Class G90 (0.9 oz. per SF)
Door Headers, Spiral Guides, Drive Shaft Support	11-ga. Hot-dipped galvanized steel	Zinc, Class G90 (Panel Wheel Guides, Aluminum)
Counterbalance Assemblies	Oil temp. Steel helical extension springs	Available up-to 8 springs per door
Weather Seals	Twin rubber, non-contact lintel	--
Solid Door Slats (avail. in 42mm, 67mm thk.)	22-ga. Hot-dipped galvanized steel, with foamed-in-place polyurethane insulation core. MicroGrain™ texture exterior, Stucco texture interior. Color RAL 9006	Zinc, Class G40 (0.4 oz. per SF) Polyurethane foam density 11pcf
Vision Door Slats (avail. in 42mm, 67mm thk.)	1" Double-pane, acrylic, clear or tinted (Obscured White, Smoke Gray) and Duratec® abrasion-resistant coating	1-5/8" or 2-5/8" Thick Vision Panel frame, extruded anodized aluminum
Ventilation Door Slats (avail. in 42mm, 67mm thk.)	1" Double-walled, perforated clear anodized aluminum, 1/2" square press-punched grid pattern	1-5/8" or 2-5/8" Thick Ventilation Panel frame, extruded anodized aluminum Open area 56.3%
Bottom Profile Door Slat (avail. in 42mm, 67mm thk.)	22-ga. Interlocking flat-faced, insulated steel panel, with weather seal loop	--
Electric Door Operator	Cast aluminum	--
Control Panel	Stainless steel, or baked-on polyester powder coat painted. Color RAL 7035 Light Gray	Powder Coat Painted, Standard
Hood and Motor Cover	Not Available	--
Energy Analysis		
Air Permeability (leakage)	0.6 cfm/ft² (12 m³h/m²), Class 2	Per test EN 12427, (ASTM E283, ANSI/NFRC 400)
Resistance to Water Penetration	Class 2, 15 min @ 55pa	Per test EN 12489 (ASTM E547)
Visible Transmittance (Tvis)	0.91%	Per calc ANSI/NFRC 200-2014 (Clear Vision Slats)
Solar Heat Gain Coefficient (SHGC)	0.75%	Per calc ANSI/NFRC 200-2014 (Clear Vision Slats)
Thermal Resistance (R-value)	Solid: R 13.6, or R 21.0, Vision: R 0.23	Per test EN 717-1, DASMA TDS-163 (Without Visions)
Heat Transfer Coefficient (U-value)	Solid: U 1.04, or U 0.64, Vision: U 4.41	Per test EN 12667: 199997-11, DASMA TDS-105
Acoustic Insulation	Solid: STC 30, R _w 26 dB, Vision: STC 34, R _w 31 dB	Per test EN 717-2, ASTM E90 (Without Visions)
LEED Credit (Potential)	EAc2, MRc1, MRc3, IEQc2, IEQc4, INc1, RPc1	USGBC® LEED v4
Electrical		
Electric Door Operator (Motor)	2.0 HP GfA Elektromaten F18	NEMA Type 3 / IP54
Operating Voltage	3 PH, 132v or 230v	--
Control Panel	5 kW variable frequency drive rated for operating voltage	NEMA Type 4X / IP66, UL/CUL Listed
Standard Power Requirement	208vAC - 600vAC, 3 PH, 60 Hz	--
Full Load Amps	13.3 A	Operator
Disconnect	Fuse: 20 Amp, Class K	Supplied by Others

Hörmann's Speed-Guardian™ High Lift, high speed, security line of doors is characterized by an attractive, elegant design with excellent obstruction avoidance capability. Double-pane vision panels provide daylighting and open views with fast operating speeds. Thanks to non-contact rolling technology along with a standard built-in light grid, the Speed-Guardian™ is a proven industry leader for both safety and longevity with versatility expressed in its range of applications in complex headroom spaces.

The Speed-Guardian™ High Lift, High speed, security line of doors provide excellent obstruction avoidance capabilities with pleasing aesthetic appeal.



Hörmann Flexon, LLC | Starpointe Business Park | 117 Starpointe Boulevard | Burgettstown, PA 15021-9506
1-800-365-3667 | 724-385-9150 | Fax: 724-385-9151 | www.hormann.us | Email: sales2@hormann.us