



Cold Storage Focus

Fabric, rubber and insulated models
for coolers, freezers, blast freezers and cold docks



Hörmann High Performance Doors

Cold storage doors defined by Hörmann quality





Partner with a global leader

As a global leader, Hörmann has 100 locations (factories and distribution) located in more than 40 countries, with more than 6,000 employees. For more than 75 years, the Hörmann Group continually strives to provide new and improved standards of quality and safety through implementing advanced door solutions to industry problems. This philosophy of excellence is evident every day through a dedication to innovation, quality and customer service.

Professional and dedicated support

Our experienced and knowledgeable sales group, comprised of regional sales managers, inside sales coordinators and a staff architect, assist you through every step of the project; from the planning stage, through answering specification questions, up to project completion and beyond. Our technical and field support department is available 365 days a year, seven days a week, which means that we are never far away. Progressive product support such as our SmartControl M2M remote monitoring system and Service Support App for installers and service technicians are available only from Hörmann and exemplify our commitment to offering our customers the most advanced door technology available today.

Fast return on investment

Fast operating speeds and highly insulated panels support energy savings. Other features such as variable frequency drive motor (soft start / soft stop), panel breakaway (fabric and rubber models), and self-reinserting panel minimize maintenance costs, providing a lower life cycle cost as compared to traditional sectional roll-up doors. Combining energy savings with lower maintenance costs and greater overall efficiency results in a timely return on investment. Ask your Hörmann door professional to complete a customized Energy Analysis Report for your application.

High Performance Doors

Cooler, freezer and food applications

TNR Chillfast

The Chillfast insulated high speed roll-up door system sustains temperature ranges suitable for cold rooms, chill rooms and freezers. Fast operating speeds minimize temperature loss in cold spaces by reducing the amount of time the door is open, for substantial savings in energy consumption.

The panel is made of 22 oz. reinforced vinyl exterior layers, dual reflective foil layers, sealed air bubble insulation with patented CutrainLoks™ and is resistant in extreme temperatures to -22°F. A heated soft bottom edge releases upon accidental impact and assists with sealing uneven floors. Modular extruded aluminum guide tracks are heated and corrosion resistant, and a pre-assembled thermal break layer minimizes air infiltration and reduces the chance for ice build-up.

The door is operated with a high-speed, 0.85 HP variable frequency direct-drive motor, for soft start / soft stop operation, minimal maintenance and low life cycle cost. Electric heater cables in hoods, guides and bottom bar have GFCI protection built into the control box which reduces the chance of electric shock and fire, ensuring safe and reliable operation. An optional heated air curtain effectively prevents ice build-up on components and walk-through areas.

SC 1400¹⁹ SEL Cool-Master

This door is ideal for energy conscious, 24/7/365 applications in agricultural, medical and cold storage facilities. An advanced 3 mm thick gray foam panel material maintains flexibility in areas over +33° F and helps keep condensation to a minimum in cooler to ambient areas. A unique sectional panel design allows for easy panel replacement for minimal downtime.

SC 1400¹⁹ SEL Food-Master

The Food-Master design allows the selection of the stainless steel options the application requires. Able to conform with all industry requirements, the following are available in stainless steel, making it possible to build a Food-Master door without paying for unnecessary options: Roll tube / hollow shaft, motor cover, guide tracks, control box and all hardware.



TNR Chillfast with insulated panel for performance to -22°F



Cool-Master with 3 mm foam panel for coolers over +33°F



Food-Master with stainless steel options for ambient areas

High Performance Doors

Blast cells, dock and ramp applications

TNR HDT Blast Cell Door

For peace-of-mind with maximum reliability in fast-paced, rugged blast cell door openings, choose the TNR HDT high performance rubber door. Process and maintenance engineers recognize the value of this product's durability and performance.

With an opening speed of 30 in/s, material handling is maximized. A knock-away bottom bar is impactable and quickly reinserted into the guide tracks following accidental impact. The frequency drive motor comes with a five-year warranty; our promise to you that this workhorse will deliver reliable performance for many years.

TNR HDD Dock Door

This basic, no-nonsense manually operated dock door provides reliable and consistent operation. A knock-away bottom bar is impactable and quickly reinserted into the guide tracks following accidental impact. A low-profile design fits into just about every application and allows for easy installation. Manual chain hoist / counterbalance operation (optional operator by others) is an affordable alternative to conventional sectional doors for loading dock openings.

Speed-Guardian™ 5000 Rigid Door for ramps to cold docks

The fast operating speeds of the Speed-Guardian™ high-speed rigid door optimizes work processes, significantly accelerates logistics processes, and reduces air exchange between controlled areas such as ramps leading to cold docks. Depending on the model, the door panel is guided into a circular bracket or into horizontal or vertical tracks. The sturdy steel sections have thermal breaks and are PU-foamed. As a result you benefit from excellent thermal values: with 1-5/8" (42 mm) thick panel R-value of 13.6 and U-value of 1.04, and minimized energy loss. For special applications that require additional energy efficiency, the Speed-Guardian™ with 2-5/8" (67 mm) thick sections is the first choice.

Our exclusive Duratec® window glazing guarantees maximum scratch resistance despite heavy use and cleaning. In addition to optional clear vision slats, all Speed-Guardian™ models have optional tinted / privacy vision slats available: Obscured White or Smoke Gray.



TNR HDT for blast cell openings provides outstanding performance in abusive environments



TNR HDD for rugged reliability in busy dock applications



Speed-Guardian™ 5000 high speed rigid door for efficiency and environmental control at ramp to cold dock locations

Hörmann and TNR models

Ultimate door solutions for coolers, freezers, blast cell freezers, dock and ramp doors

Features

● = Standard ○ = Optional - = Unavailable

Specifications	SC 1400 SEL ¹⁹ Cool-Master	SC 1400 SEL ¹⁹ Food-Master	TNR
Suitable application	Interior / Cooler	Interior / Wash-Down	
Max. width	14'0"	14'0"	
Max. height	16'0"	16'0"	
Max. opening speed (in/s)	80	80	
Closing speed (in/s)	30	30	
Minimum headroom required	17-1/4" (without hood)	17-1/4" (without hood)	
Panel			
Windlocks	-	-	
Aluminum profile	●	●	
Welded with spring steel profile	○	○	
Temperature rating of curtain	To +33° F	40 oz. material: To -22°F 90 oz. material: to - 4°F	
Resistance to wind load - Panel in closed position - In-plant only	Consult factory	Consult factory	
Breakaway	●	●	
Material	1/8" thick (3 mm)	Standard: 40 oz. / sq. yd. white Optional: 90 oz. / sq. yd. white	1/2" thick w sea
Thermal insulation U-value (metric) in W/(m ² ·K) U-value (imperial) in BTU/(h·ft ² ·°F)	Consult factory	Consult factory	
Colors	Gray	White	
Vision	●	● 40 oz. panel - 90 oz. panel	
Construction			
Hood - Galvanized steel Hood - Stainless steel	○ ○	○ ○	Sta Galva
Guide Tracks	Standard: Galvanized steel Optional: Stainless steel	Standard: Galvanized steel Optional: Stainless steel	Modul
Protection device	Light curtain	Light curtain	Heated press G
Operation			
Drive	Direct drive - Springless	Direct drive - Springless	
Electrical requirements	3-phase 208 v to 575 v	3-phase 208 v to 575 v	
Control Box	Standard: Smart Start™ NXT NEMA 4X Optional: HFCB NEMA 3 Smart Start™ NXT (1-phase, 230 v only)	Standard: Smart Start™ NXT NEMA 4X Optional: HFCB NEMA 3 Smart Start™ NXT (1-phase, 230 v only)	NEMA 4X F
Emergency opening			
Hand crank	●	●	
Chain hoist	○	○	
UPS Emergency Battery Pack (With HFCB control box only)	○	○	
Warranty			
Warranty	5 & 2 Year: 5 years motor/gearbox & panel material 2 years mechanical & electrical 1 year labor	5 & 2 Year: 5 years motor/gearbox & panel material 2 years mechanical & electrical 1 year labor	5

IR ChillFast Freezer Door	HDD Rubber Dock Door	HDT Rubber Blast Freezer Door	SG 5000 C U 42
Interior / Freezer	Interior or exterior / Dock areas	Interior or exterior / Blast cells	Interior or exterior / Ramps
13'0"	10'0"	47'0"	21'4"
18'6"	12'0"	35'0"	21'4"
108	-	12	80
36	-	12	20
37"	19"	25"	36-3/8"
-	<input type="radio"/> Curtain Lok™	<input type="radio"/> Traveling windbar up to 30 ft.	-
-	-	-	-
-	-	-	-
To -22°F	To -40°F	To -55°F	Consult factory
3 psf	Consult factory	Consult factory	Consult factory
●	●	●	-
1/2" thick 22 oz. / sq. yd. reinforced vinyl with dual reflective foil layers and closed air bubble core insulation	1/4" SBR rubber	EPDM Rubber	1-5/8" thick x 10" high galvanized steel slats
Consult factory	Consult factory	Consult factory	1.04 0.18
Blue	Black	Gray or blue	RAL 9006 on both sides of slats Custom RAL colors available
-	Optional windows 16" x 16" Maximum (1) every 5 ft. of width	Optional windows 16" x 16" Maximum (1) every 5 ft. of width	<input type="radio"/> Clear, tinted, ventilated
Standard: White lacquer finish with heater. Anodized and stainless are options.	- -	<input type="radio"/> -	<input type="radio"/> -
Extruded anodized aluminum with UHMW-PE wear strips.	Self-supporting steel angles, aluminum NEWGEN® guides	Self-supporting steel angles, aluminum NEWGEN® guides	Aluminum, circular guide with chain and springs Track dimensions: 13" w X 12" proj. Optional: horizontal, vertical, low headroom
Soft bottom edge with coil cord, pressure sensitive reversing edge. Guide-mounted photoeyes.	<input type="radio"/> Pressure sensitive reversing edge with coil cord - Upgrade	Wireless reversing edge Model HDXL 6: Thru-beam photocells Model HDXL 9: Constant pressure to close	Light curtain
Direct drive - Springless	● Manual chain hoist <input type="radio"/> Direct may be added by others	Counterbalance 50K cycle spring	Direct drive
3-phase 208 v to 575 v	-	3-phase 208 v to 575 v	Standard: 3-phase 208 v to 575 v Optional: 1-phase 230 v Optional: Step-up transformer
With e-stop, door control buttons, plug-and-play connectors	-	NEMA 4 PLC and inverter drive, soft start / soft stop	Standard: Smart Start™ NXT NEMA 4X Optional: HFCB NEMA 3 Smart Start™ with 1-phase NXT (1-phase, 230 v only)
●	-	-	-
-	●	●	●
-	-	-	<input type="radio"/>
5 years on motor/gearbox 1 year on vinyl panel	Limited lifetime on NEWGEN® Guide & Curtain Lok™ & curtain	Limited lifetime on NEWGEN® Guide & Curtain Lok™ & curtain 5 years on motor/gearbox	5 & 7 Year: 5 years motor/gearbox 2 years mechanical & electrical 7 years on vision slats against failure 1 year labor

Everything you've always wanted in a high performance door, and more

HÖRMANN

German Engineered, American Made

Our promise to you.

As one of the world's leading manufacturers of doors, we're committed to providing the best quality, value, and selection. Whether industrial or commercial, retail automotive, parking garages, transit,

waste management, fire stations or food processing, we have the door you're looking for. The Hörmann product line has a door for any application, from one manufacturer.



Hörmann High Performance Doors, Burgettstown, PA
High Performance Doors



TNR Industrial Doors, Barrie, ON, Canada
High Performance Doors

Connect with us!



Visit our website for more information!

Hörmann High Performance Doors
Starpointe Business Park • 117 Starpointe Boulevard
Burgettstown, PA 15021-9506
Phone: 800.365.3667 • 724.385.9150 • Fax: 724.385.9151
www.hormann.us • Email: info2@hormann.us



TNR Industrial Doors
200 Fairview Road, Unit 2
Barrie, ON L4N 8X8
Phone: 866.792.9968 • Fax: 705.735.9564
www.TNRdoors.com • Email: info@tnrdoors.com