



Speed-Guardian™ 5000 High Performance Door

Diverse rigid door models for various industries and applications
Interior or exterior door openings up to 21'4" w x 21'4" h



Speed-Guardian™ 5000

Various industries and applications

Features

Application	Interior or exterior *Model 5000 CV 42 sizes up to 18'0" w or maximum 224 sq.ft. (i.e. 18'0" w X 12'0" h maximum or 16'0" w X 14'0" h maximum)				
Model / Classification	5000 CV 42*	5000 U 42	5000 LP 42 springless	5000 LH 42	5000 H 67
Size range	Up to 18'0" w / 224 sq.ft	Max. 21'4" w x 21'4" h	Max. 14'0" w x 14'0" h	Max. 16'4" w x 16'0" h	Max. 16'0" w x 21'4" h
Technology	Circular guide brackets		Low profile Circular guide brackets	Low head room Horizontal tracks	High-lift tracks
Operating speed	Opening 80 IPS Closing 20 IPS		Opening 60 IPS Closing 20 IPS	Opening 80 IPS Closing 20 IPS	
Panel	Anodized aluminum 10" high x 1-5/8" (42 mm) thick slats	Galvanized steel 10" high x 1-5/8" (42 mm) thick slats.			Galvanized steel 15" high x 2-5/8" (67 mm) thick slats
All colors on RAL chart available	Smooth C0 Anodized	RAL 9006 on both exterior / interior. Exterior surface is Micrograin™, interior finish is stucco-textured			
	Optional RAL Colors: Powder-coated	Optional RAL Colors: Wet paint			
Thermal insulation U-value (metric) in W/(m ² ·K) U-value (imperial) in BTU/(h·ft ² ·°F)	4.41 0.77		1.04 0.18	Consult factory	
Vision	Standard: clear Optional: tinted	Optional: clear, perforated / ventilation, or tinted			
Mullions	Up to 144" wide, (1) Consult factory for no mullions	Up to 120" wide, none • 121" to 197" wide, (1) • 198" to 255" wide, (2)			
Resistance to wind load	Consult factory				
Guide tracks	11 ga. galvanized steel. One-piece with removable front covers. 12-5/8" wide X 12-1/8" projection				
Hood	Optional: Galvanized steel				
Safety	8'0" high light grid built into guide tracks				
Control	NEMA 4X Smart Start™ NXT, 208 to 575 v / 3-phase / 60 Hz voltage input Optional: Step-up transformer. Certain applications may require a transformer. Consult factory. Optional: HFCEB NEMA 3 Smart Start™ NXT with a 230 v / 1-phase / 60 Hz voltage input (1-phase not available on model 5000 LP 42)				
Activation options	Push button / Pull cord / Motion detector / Presence detector / Induction loop detector (wire / sealant by others) Remote control / Touchless switch (several models) Consult factory for additional options				
Accessories	LED Lite-Advance / SmartControl M2M / ScanProtect / Wireless Crash Alert / Remote Keypad / Energy Analysis Report				
Emergency	Chain hoist (Optional: Hand crank)				
Compliance	Door complies with requirements of UL325				
Warranty	5, 2 & 7 Year: Motor/gearbox (excluding catch) and panel material, 5 years, materials & workmanship. All other mechanical and electrical components free from defects, 2 years. Vision slats, 7 years against failure				



NEMA 4X Smart Start™ NXT control box simplifies installation

A distribution block accepts the activation and protection device wiring; main power cables feed through pre-drilled holes on the bottom of the box where the individual wires, with pre-wired removable terminal blocks, plug into the circuit board. Extra ports on the control board allowing for firmware upgrades and future expansion. A USB port is available for maintenance monitoring.



Thermal efficiency with clear or tinted vision slat options

The model 5000 CV 42 has a door panel made of double-pane vision slats and a non-insulated, anodized aluminum bottom slat. The insulated windows are coated with our exclusive Duratec® finish which resists marks and scratches. Vision slats are optional and available in clear, perforated / ventilation, and privacy window tints in two chic shades, Smoke Gray and Obscured White. Individual windows may be replaced without disassembling or replacing the entire vision slat.



Hörmann Flexon LLC • Starpointe Business Park • 117 Starpointe Boulevard • Burgettstown, PA 15021-9506

Phone: 800.365.3667 • 724.385.9150 • Fax: 724.385.9151 • www.hormann.us • Email: info2@hormann.us

We reserve the right to change specifications without notice. ©Hörmann Flexon LLC (Issue 03.2019)