



**GUIDE SECTION VIEW**  
(DO NOT SCALE)

\*\*HEATING CIRCUIT REQUIRES SEPARATE SOURCE 120VAC  
 \*\*\*EXTERNAL TRANSFORMER REQUIRED WHEN INCOMING POWER IS NOT 460-480V 3PH, (13"x12"x6"). PORTRAYED TRANSFORMER LOCATION FOR SIZE REFERENCE ONLY, MUST BE INSTALLED IN ACCORDANCE WITH LOCAL ELECTRICAL AUTHORITY

<b>TNR INDUSTRIAL DOORS INC.</b>	
SHOP DRAWING, CHILLFAST MODEL, LEFT HAND	
EXT. DETAIL: FREEZER DOOR - DIRECT DRIVE OPERATOR	
LIMITATIONS: (OW<=13' 0" & OH<=18' 6")	
DATE DR'N: MAR. 15, 2017	REVISION: E - JAN 20, 2021
DRAWN BY: N.M.	DRAWING No.: D-600-0144
ELECTRICAL CRITERIA: FREQUENCY INVERTER DRIVE	
CONTROL PANEL NEMA/EEMAC 4X STD. OR _____	
PRIMARY POWER SUPPLY: _____ Volts, 3 Phase, 60 Hertz	
OPERATOR CRITERIA: DIRECT DRIVE	
OPERATOR NEMA/EEMAC 3S STD. OR _____	
0.9 HP, DOOR SPEED: OPEN UP TO _____ ips, CLOSE UP TO _____ ips	
END USER:	
DEALER:	
DOOR SIZE:	SERIAL No.: TNR-

MECHANICAL OPTIONS	ELECTRICAL OPTIONS	STANDARD SYSTEM INCLUDES
<input type="checkbox"/> - AIR CURTAIN	<input type="checkbox"/> - STAINLESS CONTROL PANEL	- TIMER TO CLOSE (USER SELECT)
<input type="checkbox"/> - MOUNTED ON WARM SIDE	<input type="checkbox"/> - WIRELESS RECEIVER	- NEMA 3S OPERATOR - PLUG&PLAY
<input type="checkbox"/> - MOUNTED ON COLD SIDE	<input type="checkbox"/> - WIRELESS TRANSMITTER, QTY. _____	- NEMA4X CONTROLLER (16"W x 24"H x 8"D)
<input type="checkbox"/> - OPERATOR HOOD	<input type="checkbox"/> - N 4X, PUSHBUTTON ST'N, QTY _____	- ALUMINUM MOUNTING CHANNEL AND FRONT GUIDE
<input type="checkbox"/> - FREE END HOOD	<input type="checkbox"/> - MOTION DETECTOR, QTY. _____	- PVC GUIDE SEAL
<input type="checkbox"/> -	<input type="checkbox"/> - ADD. REFLECTIVE PHOTOEYE, QTY. _____	- HEATED GUIDES AND BOTTOM YELLOW LOOP
<input type="checkbox"/> -	<input type="checkbox"/> - PULL CORD, QTY. _____	- NON FUSED ROTARY DISCONNECT
<input type="checkbox"/> -	<input type="checkbox"/> -	- GUIDE MOUNTED THRU BEAM PHOTOEYE
<input type="checkbox"/> -	<input type="checkbox"/> -	- 22oz BLUE PVC INSULATED CURTAIN
<input type="checkbox"/> -	<input type="checkbox"/> -	- DIGITAL ENCODER LIMITS
<input type="checkbox"/> -	<input type="checkbox"/> -	- EASY RESET CURTAIN
<input type="checkbox"/> -	<input type="checkbox"/> -	- WIRELESS REVERSING EDGE
<input type="checkbox"/> -	<input type="checkbox"/> -	